



1003 CONNECTIONS



Pin No.	DESCRIPTION	VOLTAGE (VDC)
P1	B	5V
P2	V	5V
P3	Y	5V
P4	W	WHITE

1004 Encoder pin definition



PN No.	DESCRIPTION	COLOR (颜色)
PN1	SHIELD	SHIELDED(屏蔽)
PN2	B-	BRO/BLA (棕/黑)
PN3	B+	BROWN(棕)
PN4	T-	BLU/BLA(蓝/黑)
PN5	GND	BLACK(黑)
PN6	T+	BLUE(蓝)
PN7	VCC	RED(红)

Rated output 额定功率	Rated torque 额定转矩	Max Torque 最大转矩	Rated speed 额定转速	Rated current 额定电流	Power voltage 额定电压	Rotor inertia 转动惯量	Torque coefficient 转矩系数	Constant voltage 电压常数
1600W	7.5Nm	22.5Nm	2000rpm	8.0A	220V	12.4kg·cm <sup>2</sup>		

Electrical time constant 电气时间常数	Line resistance 线电阻	Line inductance 线电感	Line back EMF constant 线反电势常数	Pole-pairs 电机极对数	Encoder resolution 编码器分辨率	Insulation class 绝缘等级	Protection class 防护等级	Weight 重量
5.02ms	0.3Ω	1.506mH		5	23Bit	F	IP55	7.5 kg

比例	日期	产品名称	型号	公司名称	公司地址
1:1		110A/SW518220K-A03B-1		深圳市杰美康机电有限公司 Shenzhen Jmc Motion Control Electromechanics Co., LTD	www.jmc-motion.com www.jmc-motion.com

